



Torque-Drive® 100% Synthetic Heavy-Duty Automatic Transmission Fluid

For use in Allison,* MAN,* Voith,* ZF* and other heavy-duty transmissions.

Torque-Drive is a multi-functional fluid ideal for mixed fleets. It meets the most stringent heavy-duty transmission specifications, helping eliminate compatibility concerns and misapplication. Its advanced synthetic formulation delivers superior performance compared to its standard conventional counterparts.

Wear Protection

Transmissions operating under severe-service conditions can cause transmission fluid to break down and allow damaging metal-to-metal contact and increased wear. Torque-Drive is formulated to exceed industry requirements. Its top-of-the-line synthetic base oils and premium additives deliver superior viscosity retention and high film strength to help prevent wear and reduce operating temperatures during severe-service operating conditions.

Friction Durability

Oxidation byproducts destroy the sensitive friction characteristics of transmission fluids, resulting in the rapid degradation of shift quality. The thermal and oxidative stability inherent in Torque-Drive helps ensure consistent, smooth clutch engagement in heavy-duty applications throughout the life of the fluid. Torque-Drive maintains proper coefficients of friction, and helps prevent clutch glazing and elongated shift times.

Extreme-Temperature Performance

Hot operating conditions are no excuse for poor transmission reliability. By delivering a slower-than-normal oxidation rate, Torque-Drive helps prevent sludge that blocks small valves and varnish that restricts component movement, and reduces oil thickening that slows shift times.

In cold temperatures, Torque-Drive flows easily, as it does not contain the wax found in conventional ATFs. Cold-temperature fluidity allows for the proper operation of small, delicate, electronically controlled solenoids that affect gear changes. Transmissions using Torque-Drive have quick response times during cold operation.



- **Fights** thermal & oxidative degradation
- **Combats** sludge & varnish formation
- **Protects** against viscosity shear down
- **Flows** quickly in extreme cold
- **Delivers** excellent friction stability
- **Provides** long oil life

TYPICAL TECHNICAL PROPERTIES

AMSOIL Torque-Drive® 100% Synthetic Heavy-Duty Automatic Transmission Fluid (ATD)

Kinematic Viscosity @ 100°C, cSt (ASTM D445)	7.3
Kinematic Viscosity @ 40°C, cSt (ASTM D445)	37.1
Brookfield Viscosity @ -40°C, cP (ASTM D2983)	8278
Viscosity Index (ASTM D2270)	168
Flash Point, °C (°F) (ASTM D92)	224 (435)
Pour Point, °C (°F) (ASTM D97)	-56 (-69)
Four-Ball Wear Test (ASTM D4172) Scar, mm	0.41

PRODUCT APPLICATIONS

Use Torque-Drive in heavy-duty, on- and off-highway automatic transmissions requiring any of the following specifications:

Allison TES-295, TES-389, TES-668, C-4; **Ford** MERCON V; **GM** DEXRON III-H; **Isuzu** SCS; **JASO** 1-A; **MAN** 339 Type V-1, 339 Type V-2, 339 Type Z-1, 339 Type Z-2, 339 Type Z-3, 339F; **MB** 236.91, 236.10; **Voith** 55.6335, 55.6336; **Volvo** 97340, 97341; **ZF** TE-ML 03D, TE-ML 04D, TE-ML 14A, TE-ML 14B, TE-ML 14C, TE-ML 17C, TE-ML 20B, TE-ML 20C.

Examples of operations that benefit from using Torque-Drive include municipal or transit buses, motor coaches, garbage haulers, motor homes, delivery vans, emergency vehicles, school buses, dump trucks, utility vehicles, cement trucks, line haul trucks, tow trucks and more.

SERVICE INTERVAL

Use Torque-Drive according to the extended service interval established by the original equipment manufacturer for the performance specifications identified above under Product Applications.



PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit [AMSOIL.com/warranty.aspx](https://www.amsoil.com/warranty.aspx).

HEALTH & SAFETY STATEMENT

This product is not expected to cause health concerns when used for the intended applications and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available online at [AMSOIL.com](https://www.amsoil.com) or upon request at (715) 392-7101.

Keep Out of Reach of Children. Recycle used oil and bottle.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

